

DS-230CW

- 1/3" Sony CCD / 380 TV Lines
- 0.5 Lux @ F2.0
- Lens Option: f3.6 / 6 mm Board Lens
- Water Resistant (IP 67)
- Optional Mirror Mode

DS-230CW3.6


- Lens Option: f3.6 mm Board Lens

DS-230CW6

- Lens Option: f6 mm Board Lens



Dimensions



Specifications

Model Number	DS-230CW
Image Device	SONY 1/3" Super HAD CCD
Scanning System	2:1 Interlace
Scanning Frequency	NTSC - H: 15.734 (KHz), V: 59.94 (Hz); PAL - H: 15.635 (KHz), V: 50 (Hz)
Total Pixels	NTSC - 537(H) x 505(V); PAL - 537(H) x 597(V)
Effective Pixels	NTSC - 510(H) x 492(V); PAL - 500(H) x 582(V)
Horizontal Resolution	380 TV Lines
Electronic Shutter	NTSC - 1/60 ~ 1/100,000sec Auto; PAL - 1/50 ~ 1/100,000sec Auto
S/N Ratio	More than 46dB (AGC Off)
Signal Process	Digital Signal Processor
White Balance	Automatic (2,100 °K ~ 8,000 °K)
Sensitivity	0.5 Lux / F 2.0
Gamma Correction	=0.45
Sync System	Internal
Video Output	Composite 1[vp-p]75() unbalanced
Sensitivity	1.0 Lux / F 2.0
Sync System	Internal
Video Output	Composite 1[vp-p]75() unbalanced
Power Supply	DC12V (±10%)
Operating Temperature	-10°C ~ +50°C
Storage Temperature	-20°C ~ 60°C
Dimensions	23mm ()
Lens Options	f2.97, f3.6, f6, f8, f12mm Board lens
Remark	All models are able to be installed the Ex-View Sony CCD