




DS-D501-D



- 1/3" Sony Color CCD - **Samsung Module**
- High Resolution (**540 TVL**)
- Digital Day & Night, 4 Privacy Zones, Motion Detection
- **Built-in OSD** (On Screen Display)
- DNR (Digital Noise Reduction) for Reducing HDD capacity
- **3 Axis Camera Orientation**
- **Vari-Focal DC Auto Iris Lens** (4mm~9mm)
- Weather-proof (IP65), High-Impact Vandal Proof Dome Housing



Dimensions



www.dss.co.za

Specifications

| | |
|--|--|
| Model Number | DS-D501-D |
| Image Sensor | 1/3" Sony Super HAD CCD - Samsung Module |
| Total Pixels | 795 (H) X 596 (V) |
| Effective Pixels | 752 (H) X 582 (V) |
| Resolution | 540 TVL |
| Scanning Frequency | 15.625 KHz (H), 50 (V) |
| Shutter Speed | 1/50 ~ 1/100,000 sec |
| Minimum Illumination | Colour: 0.3 Lux (Sense-up: Auto (2x~128x)) |
| Day & Night | D&N Function by Digital Change: Auto/Off |
| Shutter | ESL / Manual / Flickerless |
| White Balance | ATW / AWC / MANUAL |
| BLC | Low / Middle / High / Off |
| AGC | Low / Middle / High / Off |
| DNR | Auto / Off |
| Privacy Zone & Motion Detection | 4 Programmable Zone |
| Sharpness | On (Level: 0 ~ 31) / Off |
| Camera ID | On / Off |
| S/N Ratio | More than 50dB |
| Video Output | Composite video output 75 ohm terminated |
| Lens | 4mm~9 mm (F:1.6) |
| Sync. System | Internal |
| Operating Humidity | 30 % ~ 90 % RH |
| Operating Temperature | - 10°C to 50°C |
| Dimension | F100 (Bubble) x 103 (H) |
| Weight | About 800g |
| Power Consumption | 180mA |
| Power Supply | 24 VDC (10.2V ~ 14.5 V) |